

Required Information

When Requesting an offer for a Protective Curtain Model VH194-NV

	0		Indoor X-ray protection for windows (Not suitable for outdoor use or as protection for doors or entrances.)			
1.	.0	Curtain Size: (If known)	cm x cm (total height including track x complete length/track length) (Fill out only after taking steps 2.1 to 4.0 into consideration . Steps 2.0, 5.0 to 6.2, and 7.0 still need to be completed!)			
2.	.0	Mounted To:	Ceiling or Wall			
2.	.1	Mounting Variation:	Inside window recess	Outside window recess		
2.	.2	Further Information:	cm Recess height cm Recess width			
2.	.3	Spacing Left: Right:	cm Recess wall to window	cm Room wall to window cm Window to room wall truct the window in a parked state.)		
3.	.0	Window Size: (Including frame)	cm x cm (H x W)	cm x cm (H x W)		
4.	.0	Window Position:	cm Upper edge of window to upper edge of recess cm Lower edge of window to lower edge of recess	 cm Upper edge of window to ceiling cm Lower edge of window to floor 		
NEW Fr	From June, 2022 – Optimized durability due to reinforced lead rubber panel suspension!					
5.		Curtain Pb-Value: (Maximum curtain length)			X-Ray Protection and Medical Suspension	
6.	.1	Panel Park Position:			Stahlgruberring 5 81829 Munich	
6	.2	osition control Panel 🔲 Right or 🔛 Left			Germany Mail Adress	
7.	.0	Additional Information: (Optional)	Please give the position and measured conditions, radiator, protruding windo		P.O. Box 820362 81803 Munich Germany	
	Ι	Important Information			Phone +49 (0) 89 / 420 96 - 0	
		 Panels in working condition: For safety, there should be an overlap of 10 cm on all sides 			Fax +49 (0) 89 / 420 96 - 200	
	 of the window. A recommended distance of 2-3 cm (min. 1 cm) from the bottom of the panels to the floor or window sill is needed so that the panels can properly move and turn. 				e-Mail info@mavig.com Web www.mavig.com	